



LIFEMOUNT™ Weigh Modules

For Tank and Hopper Weigh Systems (HYTRONIC™)

Light to Medium Capacities (300 to 50,000 lbs.)

Mild and Grade 304 Stainless Steel

Accuracy Class: 0.05%

SERIES 60-102

**LIFE/2
WARRANTY**


A SUPERIOR WEIGH MODULE WITH A SUPERIOR WARRANTY

*Designed for
long term reliability
even in harsh environments:*


- Water, heavy washdowns
- Explosive conditions
- Lightning strikes
- High corrosion
- Transient voltages and R.F.I.

Applications

- Tank & Hopper Scales
- Blender Weighing
- Conveyor Weighing
- Scissor Lift Weighing
- Custom Engineered Weigh Systems



MODEL 60-102S-10
Stainless steel,
10,000 lbs. capacity



The LIFEMOUNT Series 60-102 provides long life and unmatched performance for static and dynamic vessel weighing applications. It is designed for indoor use in low to medium weight range applications. The load cells are Hydrostatic and immune to water and electrical damage.

Customer Benefits


- Long Life - never again replace a load cell
- Superior Guarantee
- Lowest maintenance cost
- Field repairable load cell - reduced downtime
- NIST H-44 accuracy
- Low profile for easy installation
- High corrosion resistance - Grade 304 Stainless Steel
- Additional base and load plates not required

Warranty


Emery Winslow guarantees the load cell for life against damage from water and lightning and warrants it for two (2) years against damage due to normal wear and tear or defects in material and workmanship.

LIFEMOUNT Weigh Modules

SPECIFICATIONS AND DIMENSIONS



Single LIFEMOUNTS				
MODEL NO.	CAPACITY (lbs.)	DIMENSIONS (in)		
		A	B	C
60-102-3	3,000	21	5 1/2	2 7/8
60-102-10	10,000	21	7 1/2	3 1/8



EACH WEIGH SYSTEM CONSISTS OF:

- LIFEMOUNT Modules
- Totalizer
- Tubing and Cable
- Required accessories
- Engineering Review
- Instruction Manual

Series 60-102 Weigh System Selection


TOTAL SYSTEM GROSS CAPACITY RANGE - LBS.	LIFEMOUNT CAPACITY (EACH) LBS.	NUMBER OF LIFEMOUNTS	MODEL NUMBER
300 to 3,000	3,000	3	63-102-3
400 to 4,000	3,000	4	64-102-4
500 to 5,000	3,000	5	65-102-5
1,500 to 15,000	10,000	3	63-102-15
2,000 to 20,000	10,000	4	64-102-20
2,500 to 25,000	10,000	5	65-102-25

SPECIFICATIONS

- Three, four or more LIFEMOUNTS per Weigh System
- Grade 304 Stainless Steel
- Utilizes the Model 102 Hydrostatic Load Cell
- Minimum system overload capacity: 300%
- Accuracy class: 0.05%
- Low profile
- Temperature range: - 20°F to 400°F
- Factory mutual approval Class I, II, III, Division 1 and 2, Group A, B, C, D, E, F and G

CONSTRUCTION MATERIAL OPTIONS

- Grade 316 Stainless Steel
- Hastelloy and other alloys
- Aluminum / Carbon Steel



* LIFE MOUNT * ORIENTATION



INSTRUMENTS AND CONTROLS

All that is necessary to complete a Series 60-102 Weigh System is an *Emery Winslow* Digital Indicator, printer and/or controller of choice.

Emery Winslow Scale Co.

73 Cogwheel Lane
 Seymour, CT 06483 (203) 881-9333
 Fax (203) 881-9477
 E-mail: homeoffice@emerywinslow.com

4530 North 25th St.
 Terre Haute, IN 47805
 (812) 466-5265 Fax (812) 466-1046
 www.emerywinslow.com

YOUR REPRESENTATIVE IS: